

New **Stainless steel** slotted spring plunger

With ceramic ball tip

BPMc

- Positioning and locating screw

- Materials:

Body: Stainless steel 303, natural finish


Spring: Stainless steel

Ball: Ceramic (Si3N4)

Info

- Use of a Si3N4 ceramic offers high resistance and grip, is hard wearing and is chemically resistant.


stainless steel



$$\alpha = 60^\circ, F1 = 1,732x F$$

$$\alpha = 90^\circ, F1 = F$$

$$\alpha = 120^\circ, F1 = 0,577x F$$



DISCOUNTS

Qty	1+	6+	20+	50+	100+	250+	400+
Disc.	List	-5%	-10%	-15%	-30%	-50%	On request

Part number	ØD	ØD1	L	H	N	Pressure (N)		Weight (g)	Price each
						Initial F1	Finale F2		
BPM5SS/C	M5	3	12	0,9	0,8	6	11	0,9	4,90 €
BPM6SS/C	M6	3,5	14	1	1	9	13	1,5	4,90 €
BPM8SS/C	M8	5	16	1,5	1,2	15	30	3,5	6,63 €
BPM10SS/C	M10	6	19	2	1,6	20	35	7	7,58 €
BPM12SS/C	M12	8	22	2,5	2	30	55	10	11,66 €
BPM16SS/C	M16	10	24	3,5	2,5	65	125	24	14,63 €

Dimensions in mm