Spur gear for use in food industry

Module 0,5


Moulded blue PA6 Nylon

- ***Moulded gear for use in food applications***
- *Pressure angle:20°*
- *Material:*
  Blue glass-fibre reinforced Polyamide



Info

- **Pre-bore after de-moulding, must be machined before installation.*
- *Alternative numbers of teeth (up to 150) possible but minimum quantity applies.*
- ***We are unable to modify these products***



DISCOUNTS

Qty	1+	10+	20+	50+	100+
Disc.	Net	-10%	-15%	-25%	On request

Part N°	Z	ØP PCD	ØD External	ØM Hub	ØA* Pre-bore	Transmissible torque (Nm)	Price each. 1 to 9
CLG0.5-24/ALI	24	12,0	13,0	10	-	0,6	3,74 €
CLG0.5-25/ALI	25	12,5	13,5	10	-	0,6	3,77 €
CLG0.5-30/ALI	30	15,0	16,0	10	-	0,8	3,80 €
CLG0.5-32/ALI	32	16,0	17,0	10	-	0,8	3,80 €
CLG0.5-36/ALI	36	18,0	19,0	10	-	0,9	3,89 €
CLG0.5-40/ALI	40	20,0	21,0	10	-	1,0	3,89 €
CLG0.5-45/ALI	45	22,5	23,5	10	-	1,2	4,07 €
CLG0.5-48/ALI	48	24,0	25,0	10	-	1,2	4,32 €
CLG0.5-50/ALI	50	25,0	26,0	10	-	1,3	5,05 €
CLG0.5-55/ALI	55	27,5	28,5	20	-	1,4	5,67 €
CLG0.5-60/ALI	60	30,0	31,0	20	4	1,6	7,54 €

All dimensions in mm