

Conical compression spring


CDC

Stainless steel

- **Cone shaped compression spring**
- Very low height under load
- Almost uniform stiffness
- Right-hand wound
- Materials:
Stainless steel 1.4310 (301)

Advantages

- Long stroke
- Height when under load is lower than a conventional spring
- Almost constant stiffness



DISCOUNTS

Qty	1+	5+	20+	50+	75+
Disc.	Net	-5%	-10%	-15%	On request

Part N°	Wire dia ød	N° of coils	Min ext dia øDi	Max ext dia øDe	No load length Lo	Length under load	Max load	Price each.
CDC001/SS	0,30	5,00	1,80	6,00	6,00	0,30	2,60	10,90 €
CDC002/SS	0,30	6,00	1,80	6,00	9,00	0,30	2,50	10,90 €
CDC003/SS	0,30	7,20	1,80	6,00	12,00	1,00	3,50	10,90 €
CDC004/SS	0,30	3,30	2,70	6,00	3,00	0,30	1,70	10,90 €
CDC005/SS	0,30	5,00	2,70	6,00	6,00	0,60	1,30	10,90 €
CDC006/SS	0,30	6,20	2,70	6,00	9,00	0,90	1,60	10,90 €
CDC007/SS	0,40	5,00	2,40	8,00	8,00	0,40	5,00	10,90 €
CDC008/SS	0,40	6,00	2,40	8,00	12,00	0,40	5,50	10,90 €
CDC009/SS	0,40	8,00	2,40	8,00	16,00	1,60	6,40	10,90 €
CDC010/SS	0,40	3,50	3,50	8,00	4,00	0,40	2,90	10,90 €
CDC011/SS	0,40	4,60	3,50	8,00	8,00	0,40	2,90	10,90 €
CDC012/SS	0,40	6,50	3,50	8,00	12,00	1,80	3,60	10,90 €

* Subject to available stock, All dimensions in mm

DISCOUNTS

Qty	1+	5+	20+	50+	75+
Disc.	Net	-5%	-10%	-15%	On request

Part N°	Wire dia ød	N°of coils	Min ext dia øDi	Max ext dia øDe	No load lenght Lo	Lenght under load	Max load	Price each.
CDC013/SS	0,50	5,00	2,00	9,00	8,00	15,00	0,50	10,90 €
CDC014/SS	0,50	5,00	3,00	10,00	10,00	13,00	0,50	10,90 €
CDC015/SS	0,50	6,50	3,00	10,00	15,00	13,00	1,20	10,90 €
CDC016/SS	0,50	7,50	3,00	10,00	20,00	13,00	1,50	10,90 €
CDC017/SS	0,50	3,50	4,50	10,00	5,00	4,00	0,50	10,90 €
CDC018/SS	0,50	4,50	4,50	10,00	10,00	6,00	0,50	10,90 €
CDC019/SS	0,50	6,00	4,50	10,00	15,00	6,00	1,80	10,90 €
CDC020/SS	0,60	5,00	2,50	11,00	10,00	17,00	0,60	10,90 €
CDC021/SS	0,60	5,00	3,50	12,00	12,00	15,00	0,60	10,90 €
CDC022/SS	0,60	6,50	3,50	12,00	18,00	15,00	1,50	10,90 €
CDC023/SS	0,60	7,50	3,50	12,00	24,00	15,00	1,80	10,90 €
CDC024/SS	0,60	3,30	5,40	12,00	6,00	7,00	0,60	10,90 €
CDC025/SS	0,60	4,75	5,40	12,00	12,00	8,00	0,60	10,90 €
CDC026/SS	0,60	6,00	5,40	12,00	18,00	8,00	2,10	10,90 €
CDC027/SS	0,75	5,00	3,00	13,00	12,00	29,00	0,75	11,11 €
CDC028/SS	0,75	5,00	4,50	15,00	15,00	19,00	1,80	11,11 €
CDC029/SS	0,75	6,50	4,50	15,00	22,00	19,00	1,80	11,11 €
CDC030/SS	0,75	7,50	4,50	15,00	30,00	19,00	2,20	11,11 €
CDC031/SS	0,75	4,00	6,50	15,00	8,00	10,00	0,75	11,11 €
CDC032/SS	0,75	4,50	6,50	15,00	15,00	15,00	0,75	11,11 €
CDC033/SS	0,75	5,70	6,50	15,00	22,00	15,00	3,00	11,11 €
CDC034/SS	1,00	5,00	4,00	18,00	15,00	49,00	1,00	11,11 €
CDC035/SS	1,00	5,00	6,00	20,00	20,00	37,00	1,00	11,11 €
CDC036/SS	1,00	6,50	6,00	20,00	30,00	37,00	2,50	11,11 €
CDC037/SS	1,00	7,50	6,00	20,00	40,00	37,00	3,00	11,11 €
CDC038/SS	1,00	3,30	9,00	20,00	10,00	22,00	1,00	11,11 €
CDC039/SS	1,00	4,50	9,00	20,00	20,00	22,00	1,00	11,11 €
CDC040/SS	1,00	5,70	9,00	20,00	30,00	26,00	2,50	11,11 €
CDC041/SS	1,20	5,00	5,00	22,00	20,00	68,00	1,20	11,40 €
CDC042/SS	1,20	5,00	7,00	25,00	25,00	54,00	1,20	11,40 €
CDC043/SS	1,20	6,50	7,00	25,00	38,00	54,00	2,80	11,40 €
CDC044/SS	1,20	7,50	7,00	25,00	50,00	54,00	3,60	11,40 €
CDC045/SS	1,20	3,50	11,00	25,00	13,00	22,00	1,20	11,40 €
CDC046/SS	1,20	4,00	11,00	25,00	25,00	36,00	1,20	11,40 €
CDC047/SS	1,20	5,50	11,00	25,00	38,00	36,00	2,20	11,40 €

* Subject to available stock, All dimensions in mm

Fax 0 825 88 6000
Service 0,15 € / min
+ prix appel

Conical compression spring


CDC

Stainless steel

- **Cone shaped compression spring**
- Very low height under load
- Almost uniform stiffness
- Right-hand wound
- Materials:
Stainless steel 1.4310 (301)

Advantages

- Long stroke
- Height when under load is lower than a conventional spring
- Almost constant stiffness



DISCOUNTS

Qty	1+	5+	20+	50+	75+
Disc.	Net	-5%	-10%	-15%	On request

Part N°	Wire dia $\varnothing d$	N° of coils	Min ext dia $\varnothing Di$	Max ext dia $\varnothing De$	No load length Lo	Length under load	Max load	Price each.
CDC052/SS	1,50	3,50	13,00	30,00	15,00	1,50	35,00	11,40 €
CDC053/SS	1,50	4,50	13,00	30,00	30,00	1,50	56,00	11,40 €
CDC054/SS	1,50	5,50	13,00	30,00	45,00	3,30	56,00	11,40 €
CDC055/SS	1,80	5,50	7,00	32,00	30,00	1,80	156,00	11,40 €
CDC056/SS	1,80	5,50	11,00	35,00	35,00	1,80	117,00	11,40 €
CDC057/SS	1,80	7,00	11,00	35,00	52,00	4,50	117,00	11,40 €
CDC058/SS	1,80	8,00	11,00	35,00	70,00	5,40	117,00	11,40 €
CDC059/SS	1,80	3,50	16,00	35,00	18,00	1,80	45,00	11,40 €
CDC060/SS	1,80	4,30	16,00	35,00	35,00	1,80	80,00	11,40 €
CDC061/SS	1,80	6,00	16,00	35,00	52,00	3,60	90,00	11,40 €
CDC063/SS	2,00	5,50	12,00	40,00	45,00	2,00	147,00	11,40 €
CDC064/SS	2,00	7,00	12,00	40,00	68,00	5,00	147,00	11,40 €

* Subject to available stock, All dimensions in mm



DISCOUNTS

Qty	1+	5+	20+	50+	75+
Disc.	Net	-5%	-10%	-15%	On request

Part N°	Wire dia od	N°of coils	Min ext dia oDi	Max ext dia oDe	No load length Lo	Length under load	Max load	Price each.
CDC065/SS	2,00	8,00	12,00	40,00	90,00	147,00	6,00	11,40 €
CDC066/SS	2,00	3,60	18,00	40,00	22,00	60,00	2,00	11,40 €
CDC067/SS	2,00	4,70	18,00	40,00	45,00	90,00	2,00	11,40 €
CDC068/SS	2,00	6,50	18,00	40,00	68,00	120,00	4,00	11,76 €
CDC069/SS	2,00	7,50	18,00	40,00	90,00	120,00	6,00	11,76 €
CDC070/SS	2,50	5,00	10,00	45,00	40,00	310,00	2,50	11,76 €
CDC071/SS	2,50	5,00	15,00	50,00	50,00	200,00	2,50	11,76 €
CDC072/SS	2,50	6,60	15,00	50,00	75,00	200,00	6,30	11,76 €
CDC073/SS	2,50	7,50	15,00	50,00	100,00	200,00	7,50	11,76 €
CDC074/SS	2,50	4,50	22,00	50,00	25,00	60,00	2,50	11,76 €
CDC075/SS	2,50	4,50	22,00	50,00	50,00	140,00	2,50	11,76 €
CDC076/SS	2,50	6,50	22,00	50,00	75,00	190,00	6,30	11,76 €

* Subject to available stock, All dimensions in mm

Fax 0 825 88 6000
Service 0,15 € / min
+ prix appel

Altri prodotti...



PTKss
Piede speciale
agroalimentare, Inox -
3-A standard



COA-COG
Staffa di montaggio
per molla a gas,
Staffa di montaggio
piana per s...




SLS
Supporto per vite
trapezoidale,
Supporto Drylin®
fiovente



DILC
Indexing plunger with
cam, with cam



BPM-Z
Pressore a molla con
intaglio e puntale a
sfera, Corpo plastica
+ sf...



PF30
Riduttore a ruota e
vite senza fine, fino a
8.80 Nm



S2B
Supporto corto per
manicotto chiuso a
sfere, Chiuso - Corto



BHC
Vite a testa bombata
BHC , Inox A2



LRX
Guida lineare a rulli,
Binario - da 9410 N a



HSSs
Vite a spalla di
precisione inox



H2
Ingranaggio elicoidale
ad assi incrociati a



TPEf
Ruota per profili
alluminio, Fissa

Prodotti correlati



CDGamme
Molla di compressione
DIN2095, DIN 2095



R203
Molla per stampi
ISO10243, Leggero



R204
Molla per stampi
ISO10243, Medio



R205
Molla per stampi
ISO10243, Forte