Quick link

MRA


Link diameter 4-12mm

- ***For joining or closing chains***
- *Screw to secure*
- *Fully tighten to ensure safety CE and SWL markings*
- *Material:*
  Link : Steel Fe430B zinc treated
  Nut: Steel A-42-Fm



Info.

- *SWL: safe working load.*
  The Safe Working Load is calculated by dividing the Breaking Strength by a factor of safety of 5.
- ***Not sold individually, please contact us for details***



DISCOUNTS

Qty	1+	10+	20+	30+	50+
Disc.	List	-5%	-10%	-15%	On request

Part number	ØD	L2	L1	L	P	E	SWL (kg)	Weight for 100 pieces (kg)	Stock*	Price each 1 to 9
MRA1-04	4	39,5	31,5	11,5	5,5	12,5	180	1,170	-	2,84 €
MRA1-05	5	49,5	39,5	13,0	6,5	16,0	280	2,050	✔	3,23 €
MRA1-06	6	57,0	45,0	14,5	7,5	19,0	400	3,450	✔	3,81 €
MRA1-07	7	66,0	52,0	16,0	8,5	21,5	550	5,100	✔	4,80 €
MRA1-08	8	74,0	58,0	17,5	11,0	24,0	700	7,700	✔	5,52 €
MRA1-09	9	80,0	62,0	19,0	11,0	26,0	900	10,250	✔	7,45 €
MRA1-10	10	89,0	69,0	20,5	12,0	29,0	1100	13,700	✔	8,27 €
MRA1-12	12	104,5	80,5	23,5	15,0	33,0	1500	23,200	✔	11,97 €

**Depending on availability - Dimensions in mm*

Link diameter 4-12mm


MRAss

- ***For joining or closing chains***
- Screw to secure
- Fully tighten to ensure safety
- Material:
  Stainless steel 316
  Ring/nut X2CrNi



Info.

- SWL: safe working load.
  The Safe Working Load is calculated by dividing the Breaking Strength by a factor of safety of 3.



DISCOUNTS

Qty	1+	5+	10+	20+	30+
Disc.	List	-5%	-10%	-15%	On request

Part number	ØD	L2	L1	L	P	E	SWL (kg)	Weight for 100 pieces (kg)	Stock*	Price each 1 to 4
MRA1-04/SS	4	40,0	32,0	11,0	6,0	12,0	280	1,200	-	10,77 €
MRA1-05/SS	5	48,0	38,0	12,0	7,0	16,0	450	2,100	✔	12,02 €
MRA1-06/SS	6	57,0	45,0	14,0	9,0	19,0	650	3,540	✔	15,34 €
MRA1-07/SS	7	66,0	52,0	16,0	8,0	21,0	900	5,230	-	20,88 €
MRA1-08/SS	8	73,0	57,0	17,0	12,0	24,0	1100	7,900	-	20,88 €
MRA1-09/SS	9	80,0	62,0	19,0	11,0	26,0	1400	10,500	-	31,55 €
MRA1-10/SS	10	89,0	69,0	20,0	13,0	29,0	1800	14,050	-	38,19 €
MRA1-12/SS	12	105,0	81,0	23,0	16,0	34,0	2500	23,200	✔	60,81 €

**Depending on availability - Dimensions in mm*