

PERIFLEX® elastic coupling

PNA

Replacement tyre

- Tyre for PERIFLEX® coupling

- Replace the tyre without dismantling the machine
- Material natural rubber Tyre R (NR) equipped with disposed material in R
- Quality tyre X(1) with inserts mounted in X pattern

Assembly

- The elastic coupling is delivered pre-assembled. To mount the coupling, remove the tyre and place the hubs and locking assemblies on their respective shafts. Bring the two assemblies together respecting the distance "O" and aligning the two hubs with a straight edge or template.
- Place the tyre between the two hubs ensuring there is minimum radial backlash (2-15mm depending on the size of the coupling). Then bring the two locking assemblies together, tightening pairs of diametrically opposite screws to the prescribed torque. As the rubber may decompress with time, re-check the torque after a few hours.



SAVE MONEY !
Only change the tyre

DISCOUNTS

Qty.	1+	5+	10+
Disc.	List	-3%	On request

Part number spare tyre	for PERIFLEX® coupling part number	Type of tyre	Stock*	Price each 1 to 4
203R	PNA2-203	R	✓	86,27 €
206R	PNA6-206	R	✓	105,43 €
210R	PNA16-210	R	✓	159,10 €
214R	PNA40-214	R	✓	247,29 €
218R	PNA63-218	R	✓	256,88 €
414X	PNA40-214	X	-	249,22 €
418X	PNA63-218	X	-	274,13 €

*Depending on availability - Dimensions in mm

Altri prodotti...



EMR

Volantino zigrinato a serraggio rapido, Zigrinato



PWC

Inseri filettati, Kit Powercoil - con o senza attrezzo di posa



LF

Cuscinetti a sfere - Accessorio, Ghiera di regolazione




NSU

Supporto per sensore, Morsetto universale base a 90°



PRS30

Piede snodato tutto inox Ø30, Ø 30



RPP8

Cinghia di trasmissione RPP, RPP8



PPF

Pistoncino a molla, con flangia



PENC

Maniglia da incasso, montaggio a scatto




RMSA

Deceleratore, Regolabile



CHAR7530

Cerniera a molla, saldabile



G0

Ingranaggio dritto acciaio, Acciaio



GGB

Dado ad alette, Maschiato passante

Prodotti correlati



PNA

Giunto elastico PERIFLEX®, Giunto completo