

PERIFLEX® elastic coupling

PNA

Replacement tyre

- Tyre for PERIFLEX® coupling

- Replace the tyre without dismantling the machine
- Material natural rubber Tyre R (NR) equipped with disposed material in R
- Quality tyre X(1) with inserts mounted in X pattern



Assembly

- The elastic coupling is delivered pre-assembled. To mount the coupling, remove the tyre and place the hubs and locking assemblies on their respective shafts. Bring the two assemblies together respecting the distance "O" and aligning the two hubs with a straight edge or template.
- Place the tyre between the two hubs ensuring there is minimum radial backlash (2-15mm depending on the size of the coupling). Then bring the two locking assemblies together, tightening pairs of diametrically opposite screws to the prescribed torque. As the rubber may decompress with time, re-check the torque after a few hours.

SAVE MONEY !
Only change the tyre

DISCOUNTS

Qty.	1+	5+	10+
Disc.	List	-3%	On request

Part number spare tyre	for PERIFLEX® coupling part number	Type of tyre	Stock*	Price each 1 to 4
203R	PNA2-203	R	✓	86,27 €
206R	PNA6-206	R	✓	105,43 €
210R	PNA16-210	R	✓	159,10 €
214R	PNA40-214	R	✓	247,29 €
218R	PNA63-218	R	✓	256,88 €
414X	PNA40-214	X	-	249,22 €
418X	PNA63-218	X	-	274,13 €

*Depending on availability - Dimensions in mm

Altri prodotti...



CHB
Feet, For CHB gearbox



HW_HT
Guida su semi-binari,
Binario




PENC
Maniglia da incasso,
montaggio a scatto



AT5courroie
Cinghia chiusa
posizionamento AT,
AT5 Poliuretano
armatura in acciaio



JCSs
Giunto cardanico -
inox, Sollecitazioni
leggere



PRFbou
Sistema di chiusura,
Pulsante apriporta di
emergenza



LRR-53
Chiavistello con
bloccaggio, Lucchetto
a molla acciaio



BL8
Rinvio angolare, da
0.20 a 2 Nm



ZG2
Ingranaggio dritto in
plastica, Plastica



GLT3-76
Guide telescopiche
acciaio, Estensione



VELM4
Supporto avvitabile
per rotolo a strappo



BPTR
Tappo per tubo tondo,
Standard

Prodotti correlati



PNA
Giunto elastico
PERIFLEX®, Giunto
completo