

- For driving CAP881T/SS chains
- With bore and keyway
- Materials:
 - Reinforced polyamide
 - Stainless steel screws
- Operating temp.: -10°C to +120°C
- For dimensions and bore tolerances, please refer to technical pages


Advantage

- Two part design facilitates easy assembly

Easy assembly



Two part design



DISCOUNTS

| | | | |
|-------|------|-----|------------|
| Qty. | 1+ | 5+ | 10+ |
| Disc. | List | -5% | On request |

| Part number | No. of teeth | ØDE | ØDP | Bore ØA | Weight (kg) | Price each 1 to 4 |
|-------------|--------------|-----|--------|---------|-------------|-------------------|
| PT881-21-25 | 21 | 129 | 129,26 | 25 | 0,37 | 27,79 € |
| PT881-21-30 | 21 | 129 | 129,26 | 30 | 0,37 | 27,79 € |
| PT881-21-35 | 21 | 129 | 129,26 | 35 | 0,37 | 27,79 € |
| PT881-21-40 | 21 | 129 | 129,26 | 40 | 0,37 | 27,79 € |
| PT881-21-45 | 21 | 129 | 129,26 | 45 | 0,37 | 27,79 € |
| PT881-23-25 | 23 | 141 | 141,22 | 25 | 0,44 | 28,85 € |
| PT881-23-30 | 23 | 141 | 141,22 | 30 | 0,44 | 28,85 € |
| PT881-23-35 | 23 | 141 | 141,22 | 35 | 0,44 | 28,85 € |
| PT881-23-40 | 23 | 141 | 141,22 | 40 | 0,44 | 28,85 € |
| PT881-23-45 | 23 | 141 | 141,22 | 45 | 0,44 | 28,85 € |
| PT881-25-25 | 25 | 153 | 153,20 | 25 | 0,49 | 30,30 € |
| PT881-25-30 | 25 | 153 | 153,20 | 30 | 0,49 | 30,30 € |
| PT881-25-35 | 25 | 153 | 153,20 | 35 | 0,49 | 30,30 € |
| PT881-25-40 | 25 | 153 | 153,20 | 40 | 0,49 | 30,30 € |
| PT881-25-45 | 25 | 153 | 153,20 | 45 | 0,49 | 30,30 € |

Dimensions in mm

Altri prodotti...



SCH
Attrezzo di bloccaggio, A tirante orizzontale - inox



PRF_PL_4590
Elementi di giunzione, Piastra di giunzione - 45x90 mm




VRC1
Staffa di bloccaggio 1 lato, 1 lato




UGH25
Unità di guida tipo H, Per martinetti Ø25



SH0
Ingranaggio elicoidale ad assi paralleli, Acciaio 20NCD2



RPPM
Cinghia aperta al metro tipo RPP, RPP8 Poliuretano armatura in acciaio



LAT1
Attuatore lineare a motore, 1 ampere




PRF_ART
Cerniere e giunti, Standard



PTA50
Piede snodato con base stampata Ø50, 4000N



BH01
Cuscinetto radiale flangiato, Montaggio : pressione e colla



TC1rp
Tenditore per catena automatico, Con pattino 180°



PGNT
Impugnatura termoplastica a T, Con inserto maschiato

Prodotti correlati



CAP881
Catena a tapparella, Stretta serie 881



CHM30-MOT
Motoriduttore AC asincrono da 0,09 a 0,22kW, 0.09 a 0.22kW



CHMX_CHMDX
Albero per riduttore a ruota e vite senza fine CHMR e CHM, Albero se...