Locking castor with central hole

RIM


For loads up to 1000kg


- **A combination of a swivel castor and an adjustable locking support**
- Used to easily support and moving machines or other heavy equipment and then positioning them in a very stable manner.
- Installation starts by lowering the locking support using a nut.
- With the wheel no longer resting on the ground, the supported unit can be levelled despite any irregularities in the floor.
- Operating temperature range: -30 to +80°C



Materials

- Polyamide central control cross nut
- Anti-skid rubber mount allowing absorption of vibration and noise
- Body: Moulded cast aluminium body, hammered ivory paint finish
- Swivel system provided by 2 ball rings
- Mounting plate has a threaded central hole, threaded rod and nut supplied.
- Wheel: Black polyamide Shore D 70







DISCOUNTS

Qty	1+	5+	14+
Disc.	List	-5%	On request

Part number	ØA	B	H_1	H_2	ØT	Swivel interference ØK	Load (kg)	Price each 1 to 5
RIM42-60/TCE	42	20	71	81	M8	84	60	44.77 €
RIM50-280/TCE	50	25	82	92	M12	101	280	71.10 €
RIM63-550/TCE	63	28	103	118	M12	125	550	96.62 €
RIM75-800/TCE	75	30	120	132	M16	142	800	106.81 €
RIM75-1000/TCE	75	30	120	132	M16	142	1000	127.36 €

Dimensions in mm

Altri prodotti...


ACL

Angolare, Angolare orientabile


PTGR

Puleggia folle, Per cinghia tonda


PTA50

Piede snodato con base stampata Ø50, 4000N


EX

Albero per riduttori E, Albero semplice per riduttori E


ERC

Terminale rapido per cavi, A forcella


WJUM16

Pattino Drylin® W, Pattino


CHAB

Hinge with stop, Hinge


TB_ECO


Ingranaggio conico - Acciaio C43 - ECO, 3:1


BABam

Perno di sollevamento autobloccante, Autobloccante


UFX

Giunto elastico Uneflex®, economica


M1

Ruota per vite senza fine , Plastica lavorata (delrin)


E15

Riduttore a rinvio angolare, da 0.40 a 2.53 Nm

Prodotti correlati


RIMple

Ruota di livellamento, Con piastra


PDR-RD

Piede con ruota integrata, Ruota disassata