

Index bolt, weldable



SLBW

Pull to release

- Manual indexing button, smooth body, no flange

- Two versions available.

- Material :

Body: Steel 1.0403 (suitable for welding)


Pin: Hardened steel, Resistance class 5.

Head: Dark grey thermosetting plastic


Info.

- Index bolts are used where lateral movement is required to be blocked. Pulling the handle releases the pin. The M version allows the pin to be held in the retained position.

- Bolts should be welded using a WIG inert gas process.



“L” type
without
retaining
mechanism



“M” type
without
retaining
mechanism

DISCOUNTS

Qty.	1+	6+	20+
Disc.	List -10% On request		

Part number	ØD	ØD1	ØD2	L	L1	H	Fx30°	Spring force		Price each 1 to 5
								Initial (N)	Final (N)	
SLBW10-L	4	10	18	38,5	21	4	1,0	6	12	7,27 €
SLBW10-M	4	10	18	38,5	21	4	1,0	6	12	9,33 €
SLBW12-L	5	12	21	43,5	24	5	1,3	5	12	6,90 €
SLBW12-M	5	12	21	43,5	24	5	1,3	5	12	8,88 €
SLBW14-L	6	14	25	51,7	28	6	1,8	6	14	7,66 €
SLBW14-M	6	14	25	51,7	28	6	1,8	6	14	9,83 €
SLBW18-L	8	18	33	68,0	36	8	2,3	15	35	9,90 €
SLBW18-M	8	18	33	68,0	36	8	2,3	15	35	11,67 €
SLBW22-L	10	22	33	74,0	40	10	2,8	15	40	15,18 €
SLBW22-M	10	22	33	74,0	40	10	2,8	15	40	17,81 €


Altri prodotti...



Manopola, Zigrinata -
Cieco



Ruota girevole a
doppio bloccaggio,
Acciaio - poliammide



Cuscinetto in plastica,
Plastica - materiale
sfere : vetro



Chiusura a leva
regolabile, Corsa da
106,7mm a 121,4mm



Elementi di giunzione,
Piastra di
adattamento



Pomello a fungo inox,
M3 a M8



Perno autobloccante,
Acciaio



Accessori per
pannello scorrevole
per pannello scorrevole



Squadra di giunzione,
PRF19 a PRF32



Ingranaggio conico in
plastica stampata, 4:1



Guida lineare su
binario Drylin® T, fino
al 7000 N



Piede snodato con
base stampata Ø50,
4000N

Prodotti correlati



Pistoncino a molla, Da
saldare - inox



Pistoncino a molla,
Miniatura inox



Pistoncino a molla,
miniatura